

LM016L·LM016XMBL

- 16 character x 2 lines
- Controller LSI HD44780 is built-in (See page 79).
- +5V single power supply
- Display color: LM016L : Gray
LM016XMBL : New-gray

MECHANICAL DATA (Nominal dimensions)

Module size 84W x 44H x 10.5T (max.) mm
 Effective display area 61W x 15.8H mm
 Character size (5 x 7 dots) 2.96W x 4.86H mm
 Character pitch 3.55 mm
 Dot size 0.56W x 0.66H mm
 Weight about 35 g

ABSOLUTE MAXIMUM RATINGS

	min.	max.
Power supply for logic ($V_{DD}-V_{SS}$)	0	6.5 V
Power supply for LCD drive ($V_{DD}-V_O$)	0	6.5 V
Input voltage (V_i)	V_{SS}	V_{DD} V
Operating temperature (T_a)	-20	70 60*°C
Storage temperature (T_{stg})	-20	70 60*°C

* Shows the value of type LM016XMBL.

ELECTRICAL CHARACTERISTICS

$T_a = 25^\circ\text{C}$, $V_{DD} = 5.0 \text{ V} \pm 0.25 \text{ V}$

Input "high" voltage (V_{IH})	2.2 V min.
Input "low" voltage (V_{IL})	0.6 V max.
Output "high" voltage (V_{OH}) ($-I_{OH} = 0.2 \text{ mA}$)	2.4 V min.
Output "low" voltage (V_{OL}) ($I_{OL} = 1.2 \text{ mA}$)	0.4 V max.
Power supply current (I_{DD}) ($V_{DD} = 5.0 \text{ V}$)	1.0 mA typ. 3.0 mA max.

POWER SUPPLY FOR LCD DRIVE (Recommended) ($V_{DD}-V_O$)

Duty = 1/16

Range of $V_{DD}-V_O$	1.5~5.25 V
$T_a = 0^\circ\text{C}$	4.6 V typ.
$T_a = 25^\circ\text{C}$	4.4 V typ.
$T_a = 50^\circ\text{C}$	4.2 V typ.

OPTICAL DATA See page 7

INTERNAL PIN CONNECTION

Pin No.	Symbol	Level	Function
1	V_{SS}	—	0V
2	V_{DD}	—	+5V
3	V_O	—	—
4	RS	H/L	L: Instruction code input H: Data input
5	R/W	H/L	H: Data read (LCD module→MPU) L: Data write (LCD module←MPU)
6	E	H, H→L	Enable signal
7	DB0	H/L	Data bus line Note (1), (2)
8	DB1	H/L	
9	DB2	H/L	
10	DB3	H/L	
11	DB4	H/L	
12	DB5	H/L	
13	DB6	H/L	
14	DB7	H/L	

Notes:

In the HD44780, the data can be sent in either 4-bit 2-operation or 8-bit 1-operation so that it can interface to both 4 and 8 bit MPU's.

- (1) When interface data is 4 bits long, data is transferred using only 4 buses of $DB_4 \sim DB_7$ and $DB_0 \sim DB_3$ are not used. Data transfer between the HD44780 and the MPU completes when 4-bit data is transferred twice. Data of the higher order 4 bits (contents of $DB_4 \sim DB_7$ when interface data is 8 bits long) is transferred first and then lower order 4 bits (contents of $DB_0 \sim DB_3$ when interface data is 8 bits long).
- (2) When interface data is 8 bits long, data is transferred using 8 data buses of $DB_0 \sim DB_7$.




Fig. 1 Display pattern

Unit: mm




Fig. 2 External dimensions




Fig. 3 Block diagram




Fig. 4 Power supply